



Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ  
Tel : 0161 975 9002 Email : sales@friedmans.co.uk Web : www.friedmans.co.uk

## Technical Data Sheet

Article	<b>BALI RECYCLED</b>	
Composition	<b>85% POLYAMIDE (recycled) 15% ELASTANE</b>	
Weight m <sup>2</sup> (+/- 5%)	<b>210 g/m<sup>2</sup></b>	
Weight linear m. (+/- 5%)	<b>315 g/m lin.</b>	
Total width (+/- 2%)	<b>150 cm</b>	
Dimensional Stability – Washing 40° C - flat dry BS EN ISO 6330 @40°C - flat dry	width <b>-5% MAX</b>	length <b>-5% MAX</b>
Dimensional Stability – Steam	width <b>-3% MAX</b>	length <b>-3% MAX</b>
Resistance to pilling NU Martindale – ISO 12945-2 7000 rotations	on fabric <b>4/5</b>	on wool <b>3/4</b>
Hand Elongation (+/- 20%)	width <b>90%</b> (min 72% - max 108%)	length <b>135%</b> (min 108% - max 162%)
Stretch to Dynamometer (+/- 20%) INSTRON 3343 – load 1.5 kg - strip test - size of the tested sample: 100 mm x 50 mm		
Plain dyed	width <b>85%</b> (min 68% - max 102%)	length <b>130%</b> (min 104% - max 156%)
Modulus 40% - plain dyed	width <b>130-240g</b>	length <b>105-195g</b>

Care labelling codes:



Ultra-chlorine  
Resistant



Recycled Yarn



Perfect Fit



Soft



4 Way Stretch

Notes:

Technical Specification details prior to a print or foil application.

Please note due to the numerous different Industries we supply, we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests

We recommend testing each dyebath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.