



Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ  
Tel : 0161 975 9002 Email : sales@friedmans.co.uk Web : www.friedmans.co.uk

### Technical Data Sheet

Article	<b>PF1021 Renew Techno</b>	
Composition	<b>85% POLYESTER (recycled) 15% ELASTANE</b>	
Weight m <sup>2</sup> (+/- 5%)	<b>225 g/m<sup>2</sup></b>	
Weight linear m. (+/- 5%)	<b>360 g/m lin.</b>	
Total width (+/- 2%)	<b>160 cm</b>	
Dimensional Stability – Washing 40° C BS EN ISO 6330 - flat dry	width <b>-3% MAX</b>	length <b>-3% MAX</b>
Dimensional Stability – Steam	width <b>-2% MAX</b>	length <b>-2% MAX</b>
Resistance to pilling NU Martindale – ISO 12945-2 7000 rotations	on fabric <b>4/5</b>	on wool <b>3/4</b>
Stretch to Dynamometer (+/- 10%) Zwick - load 1,5 kg - strip test - size of the tested sample: 100 mm x 50 mm	width <b>105%</b> (min 95% - max 116%)	length <b>75%</b> (min 68% - max 83%)
<i>Modulus 40%</i> White for printing	width <b>240-445g</b>	length <b>285-530g</b>

Care labelling codes:



UV Protection



Perfect Fit



Excellent Coverage



Recycled Yarn

#### Notes:

Technical Specification details prior to a print or foil application.

Please note due to the numerous different Industries we supply, we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests

We recommend testing each dye bath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.