



Unit E, 3 Tudor Road, Altrincham Business Park, Cheshire, WA14 5RZ
 Tel : 0161 975 9002 Email : sales@friedmans.co.uk Web : www.friedmans.co.uk

Technical Data Sheet

Article	Smooth Velvet	
Composition	85% POLYAMIDE 15% ELASTANE	
Weight m ² (+/- 5%)	220 g/m²	
Weight linear m. (+/- 5%)	308 g/m lin.	
Total width (+/- 2%)	140 cm	
Dimensional Stability – Washing 40° C BS EN ISO 6330 – flat dry	width -5% MAX	length -5% MAX
Dimensional Stability – Steam	width -4% MAX	length -4% MAX
Resistance to pilling NU Martindale – ISO 12945-2 7000 rotations	on fabric 4/5	on wool 3/4
Hand Elongation (+/- 15%)	width 150%	length 240%
Stretch to Dynamometer (+/- 15%) INSTRON 3343 – 3.6 kg - strip test - size of the tested sample: 100 mm x 50 mm.	width 140% (min 119% - max 161%)	length 230% (min 195% - max 265%)
<i>Modulus 40%</i>	width 80-150g	length 80-180g

Care labelling codes:



Velvet



Soft



Perfect Fit



Excellent Coverage



UV Protection



Pilling Resistant



4 Way Stretch

Notes:

Technical Specification details prior to a print or foil application.

Please note due to the numerous different Industries we supply, we cannot perform tests to everyone's requirement therefore we strongly recommend you carry out your own tests

We recommend testing each dye bath before any treatment or application other than cutting and sewing. To improve our products, we reserve to modify these, as and when necessary.